



## 3 Ton Estimated Material List using 3642

Qty	Part Number	Description
1	M3642BL1-EC2	Module, Blower, S.M.A.R.T. Control, Variable Speed EC Motor, 120/208/230V
1	M3642CL1-E	Module, Refrigerant Coil (6 Row) (HP)
1	M3642CL1-H	Module, Heating (w/ Hot Water Coil)
1	UPC-61-3642	Adapter, Supply, 3642
1	UPC-24C	Drain Pan, Secondary, 3 Module, 3642
1	UPC-104-3642	Adapter, Return Air, Heat or Vertical Module 3642
1	UPC-04-3642	Return Air Duct, 18" x 10'L
1	UPC-01-3642	Filter, Grille/Return Box, 14" x 30"
3	UPC-89TM-6	TFS Install Kit, round metal plenum, Includes 6 supply outlet, w/toggles and screws, 6 take-offs, curved flange
3	UPC-38TC-W-6*	TFS, coupling, 2" duct, 12 connectors, makes 6 couplings - For white outlet face plates
3	UPC-26TC-6	Sound attenuator tubing, TFS, couplings attached 2" ID x 12'L, R-3.3 (72 ft. per box)

## 3.5 Ton Estimated Material List

Qty	Part Number	Description
1	M3642BL1-EC2	Module, Blower, S.M.A.R.T. Control, Variable Speed EC Motor, 120/208/230V
1	M3642CL1-E	Module, Refrigerant Coil (6 Row) (HP)
1	M3642CL1-H	Module, HEATING (w/ Hot Water Coil)
1	UPC-61-3642	Adapter, Supply, 3642
1	UPC-24C	Drain Pan, Secondary, 3 Module, 3642
1	UPC-104-3642	Adapter, Return Air, Heat or Vertical Module 3642
1	UPC-04-3642	Return Air Duct, 18" x 10'L
1	UPC-01-3642	Filter, Grille/Return Box, 14" x 30"
3	UPC-38TC-W-6*	TFS, Coupling, 2" Duct, 12 connectors, makes 6 couplings - for white outlet face plates
3	UPC-26TC-6	Sound Attenuator Tubing, TFS, couplings Attached 2" ID x 12'L, R-3.3 (72 ft. per box)
3	UPC-38TC-W-1*	TFS, Coupling, 2" duct, 2 connectors, makes 1 coupling - for white outlet face plates
3	UPC-26TC-1	Sound Attenuator Tubing, TFS, couplings Attached 2" ID x 12'L, R-3.3, single length (12 ft. per box)

Each material list assumes the minimum of six 12' runs per ton.

\*Couplings only required if splicing tube