


TYPICAL SYSTEM SHEETS



4 Ton Estimated Material List

Qty	Part Number	Description
1	M4860BL1-EC2	Module, Blower, S.M.A.R.T. Control, Variable Speed EC Motor, 120/208/230V
1	M4860CL1-E	Module, Refrigerant Coil (6 Row) (HP)
1	M4860CL1-H	Module, Heating (w/ Hot Water Coil)
1	UPC-61-4860	Adapter, Supply, 4860
1	UPC-24D	Drain Pan, Secondary, 3 Module, 4860
1	UPC-104-4860	Adapter, Return Air, Heat or Vertical Module 4860
1	UPC-04-4860	Return Air Duct, 20" x 10'L
1	UPC-01-4860	Filter, Grille/Return Box, 24" x 30"
4	UPC-89TM-6	TFS Install Kit, round metal plenum, includes 6 supply outlet, w/toggles and screws, 6 take-offs, curved flange
4	UPC-38TC-W-6*	TFS, Coupling, 2" duct, 12 connectors, makes 6 couplings - For white outlet face plates
4	UPC-26TC-6	Sound Attenuator tubing, TFS, couplings attached 2" ID x 12'L, R-3.3 (72 ft. per box)

5 Ton Estimated Material List

Qty	Part Number	Description
1	M4860BL1-EC2	Module, Blower, S.M.A.R.T. Control, Variable Speed EC Motor, 120/208/230V
1	M4860CL1-E	Module, Refrigerant Coil (6 Row) (HP)
1	M4860CL1-H	Module, Heating (w/ Hot Water Coil)
1	UPC-61-4860	Adapter, Supply, 4860
1	UPC-24D	Drain Pan, Secondary, 3 Module, 4860
1	UPC-104-4860	Adapter, Return Air, Heat or Vertical Module 4860
1	UPC-04-4860	Return Air Duct, 20" x 10'L
1	UPC-01-4860	Filter, Grille/Return Box, 24" x 30"
5	UPC-89TM-6	TFS Install Kit, round metal plenum, includes 6 supply outlet, w/toggles and screws, 6 take-offs, curved flange
5	UPC-38TC-W-6*	TFS, Coupling, 2" duct, 12 connectors, makes 6 couplings - for white outlet face plates
5	UPC-26TC-6	Sound Attenuator tubing, TFS, couplings attached 2" ID x 12'L, R-3.3 (72 ft. per box)

Each material list assumes the minimum of six 12' runs per ton.

*Couplings only required if splicing tube